

CleatLine[®]

Markets: Wood, Grain, Aggregates, Cement & more!

CleatLine[®] handles aggressive transfer and elevation of free flowing materials!

Features & Benefits

- ▶ Molded cleats ensure years of trouble-free service!
- ▶ No chance cleats will separate from belt
- ▶ Cleats can be made with recessed edges to accommodate skirtboarding
- ▶ Available in UsFlex[®], PSR[®], RockMaster[®] and more!
- ▶ Available in a variety of lengths

Choose from seven proven patterns!

V-Top
U-Top
C-Top
Y-Top
B-Pattern
F-Pattern
Chevron Pattern

Constantly moving forward!

www.fennerdunlopamericas.com

100% Safe Behavior & Conditions – Today

CleatLine®

CleatLine Specification Table

Carcass Style	CLEATLINE UTILITY				CLEATMASTER				PSR CLEATLINE			
	2-160		3-240		2-220		3-330		2-220		3-330	
Number of Plies	2		3		2		3		2		3	
Carcass Gauge (in ... mm)	.096	2.2	.109	2.7	.095	2.4	.130	3.3	.122	3.1	.176	4.5
Carcass Weight (lb/in/ft ... kg/m)	.035	2.0	.041	2.4	.044	2.6	.063	3.7	.054	3.2	.081	4.7
Max Tension Rating (PIW ... N/mm)	160	28	240	42	220	39	330	58	220	39	330	58
Troughing/Empty - Min Belt Width (in...mm)												
20° idlers	14	350	16	400	14	350	20	500	16	400	20	500
35° idlers	18	450	20	500	18	450	24	600	20	500	24	600
Load Support – Max Belt Width (in ... mm)												
20° idlers (0 – 40 lbs/ft ... 0 – 640 kg/m)	42	1050	54	1400	42	1050	60	1500	48	1200	60	1500
20° idlers (41 – 80 lbs/ft ... 641 -1280 kg/m)	36	900	48	1200	36	900	54	1400	42	1050	54	1400
20° idlers (81 – 120 lbs/ft ... 1281 -1920 kg/m)	30	750	42	1050	30	750	42	1050	36	900	48	1200
35° idlers (0 – 40 lbs/ft ... 0 – 640 kg/m)	36	900	48	1200	36	900	54	1400	42	1050	54	1400
35° idlers (41 – 80 lbs/ft ... 641 -1280 kg/m)	30	750	42	1050	30	750	48	1200	36	900	48	1200
35° idlers (81 – 120 lbs/ft ... 1281 -1920 kg/m)	24	600	36	900	24	600	42	1050	30	750	42	1050
Minimum Pulley Diameters (in ... mm)												
81 – 100% belt rated tension	14	350	16	400	16	400	20	500	16	400	20	500
61 – 80% belt rated tension	12	300	14	350	14	350	18	450	14	350	18	450
Up to 60% belt rated tension	10	250	12	300	12	300	14	350	12	300	16	400

**Contact your local Fenner Dunlop
Distributor to place your orders today!**

Visit www.fennerdunlopamericas.com to find your local distributor.

